MOTOR DATA SHEET

MOTOR PART CODE: **1.543TECCB3-IE3**

FRAME SIZE: **90L-4**

	50Hz
Output (kW)	1.5
Rotation Speed (rpm)	1430
Voltage	230/400
Full Load Current (A)	6.28 | 3.63
Full Load Torque (Nm)	10.02

	60Hz
Output (kW)	1.8
Rotation Speed (rpm)	1716
Voltage	276 | 480
Full Load Current (A)	6.28 | 3.63
Full Load Torque (Nm)	8.35

Efficiency Data

100%	75%	50%
85.3	86.1	85.2

Factory Reference	T3C 90L-4
Tst/Tn (times)	2.8
Tmax/Tn	3
Noise (dB)	61
Moment of inertia	0.00469
Type of feet	Removable feet
Protection	IP55
Rotation Direction	F / R
Cable Glands	1 - M20× 1.5
Paint Colour	RAL 7024
Efficiency	IE3
Bearing (DE)	6205 2RS C3

Power Factor (cos)	0.7
Tmin/Tn	2.2
Ist/In (Times)	7.3
Net Weight (Kg)	26.3
Housing material	Cast Iron
Insulation Class	F
Thermal Protection	PTC 140°C
Duty Cycle	S1
Cooling	IC411
Ambient Temperature	-20°C to +40°C
Bearing Brand	NSK
Bearing (NDE)	6205 2RS C3

Motors designed and manufactured in accordance with:

IEC 60034
IEC 60038
IEC 60072
2014/30/EU (EMC)
2014/35/EU (LVD)
2011/65/EU (RoHS 2)

www.tecmotors.co.uk

TEC Electric Motors Ltd. reserves the right to amend or change motor designs or data sheet information