



Figure similar

MLFB-Ordering data

6SL3120-2TE21-8AA3

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data		Ambient conditions	
DC link voltage	DC 510 ... 720 V	Installation altitude (without derating)	1000 m (3281 ft)
Electronics power supply	DC 24 V -15 % / +20 %	Cooling ⁸⁾	Internal air cooling
Current demand, max.	1.00 A	Cooling air requirement	0.016 m ³ /s
DC-link current I _d	43.0 A	Ambient temperature	
Output current		During operation	
Rated value I _N	2 x 18.0 A	0 ... 40 °C (32 ... 104 °F)	
Base load current I _H	2 x 15.3 A	Connections	
For S6 duty (40%) I _{S6}	2 x 24.0 A	Motor end	
I _{max}	2 x 36.0 A	Version	
Type rating ²⁾		connector (X1, X2)	
Based on I _N	2 x 9.7 kW	PE connection	
Based on I _H	2 x 8.2 kW	M5 screw	
Current carrying capacity		Shield connecting kit	
DC link busbars	100 A	Integrated connection plug (X1, X2)	
24 V busbars ⁴⁾	20 A	Max. motor cable length	
DC link capacitance	705 μF	Shielded	
		70 m (230 ft)	
		Unshielded	
		100 m (328 ft)	
		Standards	
		Compliance with standards	
		CE, cULus	
		Safety Integrated	
		SIL 2 acc. to IEC 61508, PL d acc. to EN ISO 13849-1, Category 3 acc. to EN ISO 13849-1	

MLFB-Ordering data

6SL3120-2TE21-8AA3



Figure similar

Mechanical data

Line side

Width	100.00 mm (3.94 in)
Height	380.00 mm (14.96 in)
Depth	270.00 mm (10.63 in)
Degree of protection	IP20 / UL open type
Type of construction	Booksize
Net weight	6.8 kg (14.99 lb)

General tech. specifications

Sound pressure level (1m)	60.0 dB
Power loss, typ./max. ⁹⁾	0.28 kW / 0.35 kW

2) Rated output of a typical standard asynchronous motor at 400 V 3 AC

4) If, when connecting several Line Modules and Motor Modules in series, the current carrying capacity exceeds 20 A, another 24 V DC connection is required using a 24 V terminal adapter (max. connectable cross-section 6 mm², max. protection 20 A).

8) Power units with intensified air cooling thanks to integrated fan

9) Power loss of the Motor Module with rated power including losses of the 24 V DC electronics power supply